

Adaptive Ai Camera

FaceCam™



Product Code: FC-FSHC01

AI POWERED IMAGE SENSOR

- Demographic data from visitors (Age, Gender, Mood)
- Customer base profiling
- Extra low power consumption with low-duty cycle
 Camera sensor with GDPR compliant
 Data processed locally, result transmit through Wi-Fi or BLE
- Configurable features to include or exclude matrix through FootfallCam Analytic Manager V9™

ACCURATE DEMOGRAPHIC PROFILE WITH STAFF EXCLUSION

 With provided staff faces, FaceCam[™] is able to exclude demographic data generated by staff without affecting the daily operation.

VISITOR PROFILE AND TRAFFIC ANALYSIS

 Generate demographic data with visitors passed by, numerous data collected with location, number of people, date and time.

MARKETING EFFECTIVENESS


 Optimise marketing activities by understanding the marketing campaign effectiveness versus the profiling and catchment area profiling.

TECHNICAL DATA

Device Dimension (mm)	34 (W) x 20 (D) x 64 (H)
Weight	Device: 0.580 kg Packing: 1.68 kg
Camera	2MP (1632 x 1232), 68°, 2MP
	omni-vision 2640 camera modules
Indicator	RGB LED status indicator
Casing	Made by PC Plastic
Ideal Mounting Height	1.6 m – 2 metres
Operating Environment	Temperature 10°C to 45°C, Humidity 10% - 90%
Storage Environment	Temperature -40°C to 80°C, Humidity 10% - 95%
Tracking Technology	Image Processing with Deep Learning. Collects colour image data.
Field Upgradable	Manual / Auto Software upgrade
Interface	2.4GHz Wi-Fi and Bluetooth
Voltage	7~12V
Power Consumption	Average 0.8W
1,1,2,11	Maximum 1.3W
Power Supply	5V DC
Cabling	14~26 AWG
Warranty	1-year Manufacturer Warranty
Origin	Made in the UK

Notes

PRODUCT DIMENSION



One FootfallCam FaceCam™ camera must be mounted covering the entire face of the people passing by.